



Power Over Ethernet High Definition Megapixel IP Camera

### DESCRIPTION



Add-On Camera for First Alert HD PoE IP NVR\*

2-Pack - 2MP PoE HD IP 1/3" Progressive Scan CMOS Color Indoor/Outdoor Camera with Auto IR Cut Filter and Cold Temperature Performance



- HIGH DEFINITION PoE HD CAMERA
- POWER OVER ETHERNET
- INDOOR/OUTDOOR
- NIGHT VISION
- AUTO IR CUT FILTER
- COLD TEMP PERFORMANCE

**First Alert**<sup>®</sup>**CONTENTS:**

- 2 2MP PoE HD IP Color Cameras
- 2 Mounting Kits
- 2 100' Cat5e cables
- 1 User Manual
- 3 Window Warning Decals

**PRODUCT SPECIFICATIONS****Camera**

Power Supply/Consumption	DC 12V/Max 7W , PoE (802.3af)
Operating Temp	-22°F to +140°F ( -30°C to +60°C)
Humidity	95% or less (Non-condensing)
Dimensions (Camera & Stand)	2.3" (58.4mm) x 2.3" (58.4mm) x 6.5" (165.1mm)
Weight	0.94 lbs. (426g)
Color:	White
Communication Interface	1 RJ45 10M/100M Ethernet
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, BONJOUR
Security	User Authentication, Watermark
Standard	ONVIF, PSIA, CGI, ISAPI
Image Sensor	1/3" Progressive Scan CMOS
IR Cut Filter	Automatic
Lens	4mm
View Angle	79°
Number of Effective Pixels	NTSC - 1920 x 1080
Indoor/Outdoor	Both
Weather Resistant Rating	IP66
Digital Noise Reduction	3D DNR
Wide Dynamic Range	Digital WDR
Dual Stream	Yes
Image Settings	Rotate mode, saturation, bright ness, contrast adjustable by client software of web browser.
Privacy Mask	Yes, Up To 4 Configurable Areas
Backlight Compensation	Auto
Minimum Illuminance	0.07 LUX @ (F1.2, AGC ON), 0 LUX with IR on
Video Frame Rate	30FPS
Video Bit Rate	32 KBPS – 8 MBPS
Video Compression	H.264/MJPEG
Shutter Speed	1/30 - 1/100,000 second
Audio	No
Color	Yes

**Night Vision**

Number of infrared LED's	30
Distance	98 ft (30m)

\*Note: Add-on camera to be used with First Alert HD-HD PoE IP NVR 's. No power supply is included. Power is obtained from the NVR through the power over ethernet connection (PoE).

**SHIPPING SPECIFICATIONS****Individual Carton**

Dimensions	9.93"L x 8.5"W x 7.63"H
Weight	5.83 lbs.
Cube	0.37 ft3
UPC	0 29054 01506 8

**Master Carton**

Dimensions	9.93"L x 8.5"W x 7.63"H
Master Pack	1 (2 Pack)
Weight	5.83 lbs.
Cube	0.37 ft3
I2of5	100 29054 01506 5

**Pallet Information**

Cases per layer	20
Number of Layers	6
Cases per Pallet	120
Units per Pallet	120
Cube	50.1 ft3
Weight	766 lbs.

**BRK**<sup>®</sup>

THE PROFESSIONAL STANDARD

brkelectronics.com

©2015 BRK Brands, Inc.  
a Jarden Corporation Company (NYSE:JAH)  
3901 Liberty Street Road, Aurora, IL 60504-8122  
Phone: 630-851-7330 Tech Services: 800-323-9005  
First Alert is a registered trademark of the First Alert Trust  
BRK is a registered trademark of BRK Brands, Inc.  
CM3263