



Power Over Ethernet High Definition Megapixel IP Camera

DESCRIPTION



Add-On Camera for First Alert HD PoE IP NVR*

3MP PoE HD IP , 360 Panoramic View, Virtual PTZ
1/3" Progressive Scan CMOS Color
Indoor/Outdoor Camera with Auto IR Cut Filter
and Cold Temperature Performance



- HD**
HIGH DEFINITION PoE HD CAMERA
- PoE**
POWER OVER ETHERNET
- INDOOR/OUTDOOR**
- NIGHT VISION**
- AUTO IR CUT FILTER**
- COLD TEMP PERFORMANCE**

First Alert®**CONTENTS:**

- 1 3MP PoE HD IP 360 View, Virtual PTZ Color Camera
- 1 Mounting Kit
- 1 100' Cat5e cable
- 1 User Manual
- 3 Window Warning Decals

PRODUCT SPECIFICATIONS**Camera**

Power Supply/Consumption	DC 12V/Max 7W , PoE (802.3af)
Operating Temp	-22°F to +140°F (-30°C to +60°C)
Humidity	95% or less (Non-condensing)
Dimensions (Camera & Stand)	6.6" Dia. (166.7mm) x 1.8" H (44.5mm)
Weight	1.38 lbs. (624g)
Color:	White
Communication Interface	1 RJ45 10M/100M Ethernet
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, BONJOUR
Security	User Authentication, Watermark
Standard	ONVIF, PSIA, CGI, ISAPI
Image Sensor	1/3" Progressive Scan CMOS
IR Cut Filter	Automatic
Lens	1.19mm, F2.0
View Angle	360°
Max Resolution	NTSC - 1536 x 1536
Indoor/Outdoor	Both
Weather Resistant Rating	IP66
Digital Noise Reduction	3D DNR
Wide Dynamic Range	Digital WDR
Dual Stream	Yes
Multi-Channel Mode	1 × fisheye (1536 × 1536, 20fps), 1 × panoramic (1600 × 1200, 20fps), 3 × PTZ (800 × 600, 20fps).
Privacy Mask	Yes, Up To 4 Configurable Areas per each of 5 multi-channel mode
Backlight Compensation	Auto
Minimum Illuminance	0.07 LUX @ (F1.2, AGC ON), 0 LUX with IR on
Video Frame Rate	30FPS
Video Bit Rate	32 KBPS – 16 MBPS
Audio Codec	G.711/G.726
Video Compression	H.264/MJPEG
Shutter Speed	1/30 - 1/100,000 second
Audio	Yes
Color	Yes
Storage	Supports up to 64GB Micro SD/ SDHC card

Night Vision

Number of infrared LED's	3
Distance	49 ft (15m)

*Note: Add-on camera to be used with First Alert HD-HD PoE IP NVR 's. No power supply is included. Power is obtained from the NVR through the power over ethernet connection (PoE).

SHIPPING SPECIFICATIONS**Individual Carton**

Dimensions	11.00"L x 8.75"W x 3.13"H
Weight	3.9 lbs.
Cube	0.17 ft3
UPC	0 29054 01462 7

Master Carton

Dimensions	11.0"L x 8.75"W x 3.13"H
Master Pack	1
Weight	3.9 lbs.
Cube	0.17 ft3
I2of5	100 29054 01462 4

Pallet Information

Cases per layer	17
Number of Layers	8
Cases per Pallet	136
Units per Pallet	136
Cube	50.3 ft3
Weight	601 lbs.

BRK®

THE PROFESSIONAL STANDARD
brkelectronics.com

©2015 BRK Brands, Inc.
a Jarden Corporation Company (NYSE:JAH)
3901 Liberty Street Road, Aurora, IL 60504-8122
Phone: 630-851-7330 Tech Services: 800-323-9005
First Alert is a registered trademark of the First Alert Trust
BRK is a registered trademark of BRK Brands, Inc.
CM3262